



Super-247™
Lead Free and RoHS Compliance Document

Contents:

1. Composition
2. Tin Whisker Report
3. RoHS Certification
4. Independent Laboratory Analysis



Super 247

Component	Material Name	Material Mass (gr/ea)	Element Name Composition	Substance Mass (per device) G	Material Analysis Weight (%)	% of Total Weight
Chip	Silicon	0.05530	Si	0.05530	100%	0.9%
Encapsulant	Epoxy Resin	0.81510	SiO2	0.66268	81%	10.4%
			Epoxy	0.06521	8%	1.0%
			Other	0.08722	11%	1.4%
Lead Frame	Copper	5.35810	Cu	5.33131	100%	83.6%
			Other	0.02679	0%	0.4%
Die Attach	J-Alloy	0.02730	Sn	0.01775	65%	0.3%
			Ag	0.00683	25%	0.1%
			Sb	0.00273	10%	0.0%
Wire bond	Aluminum	0.04780	Al	0.04780	100%	0.7%
Lead Finish	Matte Tin	0.07060	Sn (PBF)	0.07060	100%	1.1%

Total Weight (g) **6.37422**

This part is compliant with EU Directive 2002/95/EC (RoHS) and does not contain lead, mercury, cadmium (0.01%), hexavalent chromium, PBB or PBDE in concentrations greater than 0.1%, except as permitted by Annex (7).

Data for IR products and services contained in this document was derived under specific operating and environmental conditions. The actual results obtained by any other party implementing such products or services will depend on a large number of factors and may vary significantly. IR makes no representation that these results can be expected or obtained by any other party. The information contained in this document is provided without any warranty, either expressed or implied, and IR specifically disclaims any and all liability, including but not limited to consequential or indirect damages. IR reserves the right to make changes without further notice to any products and services contained herein.



Super 247 Tin Whisker Report

Objective: To evaluate the Tin whisker growth for various test conditions on PBF products

Part No: IRF614

Package Type: TO-220

TO-220 used as the test vehicle

Test	Room Temperature Storage	Temperature Humidity Unbias	Bake
Test Conditions	30+/-2°C, 60+/-3%RH	60+/-5°C, 85+3/-2%RH	55°C
Test Status / Readpoint	WFA / 6 mo	NWF / 6 mo	WFA / 6 mo

Examples:

Whisker Length (µm)	15	12	9

Abbreviation	NWF	WFA	WFO
Whisker length pass/fail criterion	No Whiskers Found Whisker length less than 10 um is considered insignificant	Whiskers found within acceptable range Whisker length less than 40 um is considered pass	Whiskers found over acceptable range Whisker length exceeding 40 um is considered fail

Sn Plating descriptions:

Plating thickness (µin): >300 to 800

Annealing conditions: N/A

Plating finish: 100% Sn Matte

Sample size: 3 pieces per test

Reflow: N/A

Data for IR products and services contained in this document was derived under specific operating and environmental conditions. The actual results obtained by any other party implementing such products or services will depend on a large number of factors and may vary significantly. IR makes no representation that these results can be expected or obtained by any other party. The information contained in this document is provided without any warranty, either expressed or implied, and IR specifically disclaims any and all liability, including but not limited to consequential or indirect damages. IR reserves the right to make changes without further notice to any products and services contained herein.

International IOR Rectifier


International Rectifier components and their homogeneous sub-components manufactured under the Lead Free Program ⁽¹⁾ are in compliance with European Union Directive 2002/95/EC (RoHS Directive) of the European Parliament and of the Council of 27 January 2003. IR parts that have been identified as RoHS compliant do not exceed the maximum limit for following 6 designated substances.

Substance	Maximum Limit (ppm)
Cadmium (Cd)	100
Lead (Pb)	1000 ⁽²⁾
Mercury (Hg)	1000
Hexavalent Chromium (Cr ⁶⁺)	1000
Poly Brominated Biphenyls (PBB)	1000
Poly Brominated Diphenyl Ethers (PBDE)	1000


- (1) Part numbers typically contain a "PBF" suffix
- (2) Maximum limit (ppm) does not apply to applications for which exemptions have been granted by the RoHS Directive

Our statements in this letter regarding RoHS compliance and lead content do not extend to, or apply to any product subjected to unintended contamination, misuse, neglect, accident, improper installation, or to use in violation of instructions furnished by IR. We additionally note that IR products in certain specific large outline packages could contain high temperature solder die attach material having greater than 85% lead content, which is considered exempt from ELV Directive, Article 4(2)(a) by Annex II and RoHS Directive, Article 4(1) by Annex (7).

Authorized signatures for International Rectifier:

Name:  Greg Takagi Date: 8/22/2005

Position: Director, Global Environmental Health and Safety

Name:  Danny Narabal Date: 8/23/05

Position: Director, Package Engineering

The information contained in this letter is being provided for informational purposes only and to clarify certain information concerning IR products. Nothing provided in this letter is (i) a representation, warranty or agreement to indemnification by IR, (ii) a statement which may form the basis of reliance by IR, (iii) a modification of any of the terms and conditions of sale agreed to in writing between IR and its customers with respect to any IR products, whether previously sold or to be sold in the future.

Results:

	PBB/PDBE	Cr(VI)	PVC	Asbestos
Sample Name	ppm (wt.)	ppm (wt.)	ppm (wt.)	P/NP
Blank	<10.	<1.0	<1.0	NP
IRF4905PBF (TO-220)	<10.	<1.0	<1.0	NP
IRFP450PBF (TO-247)	<10.	<1.0	<1.0	NP
IRF740SPBF (D2-PAK)	<10.	<1.0	<1.0	NP
IRFR3707ZPBF (D-PAK)	<10.	<1.0	<1.0	NP
IRLL2705PBF (SOT-223)	<10.	<1.0	<1.0	NP
IRF6603 (DirectFET)	<10.	<1.0	<1.0	NP
IRLML6401TRPBF (Micro-3)	<10.	<1.0	<1.0	NP
IRLMS6802TRPBF (Micro-6)	<10.	<1.0	<1.0	NP
IRF7821PBF(SO-8)	<10.	<1.0	<1.0	NP
IR2153PBF (8L PDIP)	<10.	<1.0	<1.0	NP
IRF7503TRPBF (Micro-8)	<10.	<1.0	<1.0	NP
IR3086AMPBF (20L MLPQ)	<10.	<1.0	<1.0	NP