



#### Features

- Package fully compatible with the industry standard INT-A-pak power modules series
- High thermal conductivity package, electrically insulated case
- Excellent power volume ratio
- 4000 V<sub>RMS</sub> isolating voltage
- UL E78996 approved 
- TOTALLY LEAD-FREE



#### Description

A range of extremely compact, encapsulated three phase bridge rectifiers offering efficient and reliable operation. They are intended for use in general purpose and heavy duty applications.

#### Major Ratings and Characteristics

Parameters	130MT.K	160MT.K	Units
$I_o$	130(160)	160(200)	A
@ $T_c$	85(62)	85(60)	°C
$I_{FSM}$	1130	1430	A
@50Hz	1180	1500	A
@60Hz	6400	10200	A <sup>2</sup> s
$I^2t$	5800	9300	A <sup>2</sup> s
@50Hz	64000	102000	A <sup>2</sup> /s
@60Hz			
$I^2\sqrt{t}$			
$V_{RRM}$ range	800 to 1600		V
$T_{STG}$ range	-40 to 150		°C
$T_J$ range	-40 to 150		°C

## 130-160MT..KPbF Series

Bulletin I27216 03/06

International  
**IRF** Rectifier

### ELECTRICAL SPECIFICATIONS

#### Voltage Ratings

Type number	Voltage Code	$V_{RRM}$ , maximum repetitive peak reverse voltage V	$V_{RSM}$ , maximum non-repetitive peak rev. voltage V	$I_{RRM}$ max. @ $T_J$ max. mA
130-160MT..K	80	800	900	10
	100	1000	1100	
	120	1200	1300	
	140	1400	1500	
	160	1600	1700	

#### Forward Conduction

Parameter	130MT.K	160MT.K	Units	Conditions																	
$I_O$ Maximum DC output current @ Case temperature	130 (160) 85 (62)	160 (200) 85 (60)	A °C	120° Rect conduction angle																	
$I_{FSM}$ Maximum peak, one-cycle forward, non-repetitive surge current	1130 1180 950 1000	1430 1500 1200 1260	A	<table border="1"> <tr> <td>t = 10ms</td> <td>No voltage</td> <td rowspan="8">Initial <math>T_J = T_J</math> max.</td> </tr> <tr> <td>t = 8.3ms</td> <td>reapplied</td> </tr> <tr> <td>t = 10ms</td> <td>100% <math>V_{RRM}</math></td> </tr> <tr> <td>t = 8.3ms</td> <td>reapplied</td> </tr> <tr> <td>t = 10ms</td> <td>No voltage</td> </tr> <tr> <td>t = 8.3ms</td> <td>reapplied</td> </tr> <tr> <td>t = 10ms</td> <td>100% <math>V_{RRM}</math></td> </tr> <tr> <td>t = 8.3ms</td> <td>reapplied</td> </tr> </table>	t = 10ms	No voltage	Initial $T_J = T_J$ max.	t = 8.3ms	reapplied	t = 10ms	100% $V_{RRM}$	t = 8.3ms	reapplied	t = 10ms	No voltage	t = 8.3ms	reapplied	t = 10ms	100% $V_{RRM}$	t = 8.3ms	reapplied
t = 10ms	No voltage	Initial $T_J = T_J$ max.																			
t = 8.3ms	reapplied																				
t = 10ms	100% $V_{RRM}$																				
t = 8.3ms	reapplied																				
t = 10ms	No voltage																				
t = 8.3ms	reapplied																				
t = 10ms	100% $V_{RRM}$																				
t = 8.3ms	reapplied																				
$I^2t$ Maximum $I^2t$ for fusing	64000 5800 4500 4100	10200 9300 7200 6600	A <sup>2</sup> s	<table border="1"> <tr> <td>t = 10ms</td> <td>No voltage</td> <td rowspan="8">Initial <math>T_J = T_J</math> max.</td> </tr> <tr> <td>t = 8.3ms</td> <td>reapplied</td> </tr> <tr> <td>t = 10ms</td> <td>100% <math>V_{RRM}</math></td> </tr> <tr> <td>t = 8.3ms</td> <td>reapplied</td> </tr> <tr> <td>t = 10ms</td> <td>No voltage</td> </tr> <tr> <td>t = 8.3ms</td> <td>reapplied</td> </tr> <tr> <td>t = 10ms</td> <td>100% <math>V_{RRM}</math></td> </tr> <tr> <td>t = 8.3ms</td> <td>reapplied</td> </tr> </table>	t = 10ms	No voltage	Initial $T_J = T_J$ max.	t = 8.3ms	reapplied	t = 10ms	100% $V_{RRM}$	t = 8.3ms	reapplied	t = 10ms	No voltage	t = 8.3ms	reapplied	t = 10ms	100% $V_{RRM}$	t = 8.3ms	reapplied
t = 10ms	No voltage	Initial $T_J = T_J$ max.																			
t = 8.3ms	reapplied																				
t = 10ms	100% $V_{RRM}$																				
t = 8.3ms	reapplied																				
t = 10ms	No voltage																				
t = 8.3ms	reapplied																				
t = 10ms	100% $V_{RRM}$																				
t = 8.3ms	reapplied																				
$I^2\sqrt{t}$ Maximum $I^2\sqrt{t}$ for fusing	64000	102000	A <sup>2</sup> √s	t = 0.1 to 10ms, no voltage reapplied																	
$V_{F(TO)1}$ Low level value of threshold voltage	0.78	0.81	V	$(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$ , @ $T_J$ max.																	
$V_{F(TO)2}$ High level value of threshold voltage	0.99	1.04	V	$(I > \pi \times I_{F(AV)})$ , @ $T_J$ max.																	
$r_{f1}$ Low level value of forward slope resistance	4.59	3.52	mΩ	$(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$ , @ $T_J$ max.																	
$r_{f2}$ High level value of forward slope resistance	4.17	3.13	mΩ	$(I > \pi \times I_{F(AV)})$ , @ $T_J$ max.																	
$V_{FM}$ Maximum forward voltage drop	1.63	1.49	V	$I_{pk} = 200A$ , $T_J = 25^\circ C$ , $t_p = 400\mu s$ single junction																	
$V_{INS}$ RMS isolation voltage	4000	4000	V	$T_J = 25^\circ C$ , all terminal shorted f = 50Hz, t = 1s																	

#### Thermal and Mechanical Specifications

Parameter	130MT.K	160MT.K	Units	Conditions
$T_J$ Max. junction operating temperature range	-40 to 150		°C	
$T_{stg}$ Max. storage temperature range	-40 to 150		°C	
$R_{thJC}$ Max. thermal resistance, junction to case	0.16 0.93 0.18 1.08	0.12 0.73 0.15 0.88	K/W	DC operation per module DC operation per junction 120° Rect conduction angle per module 120° Rect conduction angle per junction
$R_{thCS}$ Max. thermal resistance, case to heatsink	0.03		K/W	Per module Mounting surface smooth, flat and greased
T Mounting torque $\pm 10\%$ to heatsink to terminal	4 to 6 3 to 4		Nm	A mounting compound is recommended and the torque should be rechecked after a period of 3 hours to allow for the spread of the compound. Lubricated threads.
wt Approximate weight	176		g	









