

Major Ratings and Characteristics

Characteristics	1N7064CCU3	Units
$I_{F(AV)}$	30	A
V_{RRM} (Per Leg)	45	V
I_{FSM} @ tp = 8.3ms half-sine (Per Leg)	85	A
V_F @ 30Apk, $T_J = 125^\circ\text{C}$ (Per Leg)	0.95	V
T_J, T_{STG} Operating and Storage	-65 to 150	$^\circ\text{C}$

Description/Features


The 1N7064CCU3 center tap Schottky rectifier has been expressly designed to meet the rigorous requirements of HiRel environments. It is packaged in the hermetic surface mount SMD-0.5 ceramic package. The device's forward voltage drop and reverse leakage current are optimized for the lowest power loss and the highest circuit efficiency for typical high frequency switching power supplies and resonant power converters. Full MIL-PRF-19500 quality conformance testing is available on source control drawings to TX, TXV and S quality levels.

Additional Product Summary (Parts with Ceramic Lids) *

Part Number
30CLJQ045
JANTX1N7064CCU3C
JANTXV1N7064CCU3C
JANS1N7064CCU3C

- Hermetically Sealed
- Center Tap
- Low Forward Voltage Drop
- High Frequency Operation
- Guard Ring for Enhanced Ruggedness and Long Reliability
- Surface Mount
- Lightweight

* Refer to Page 5 for Case Outline and Dimensions of SMD-0.5 with Ceramic Lid



Voltage Ratings

Part number	1N7064CCU3
V _R Max. DC Reverse Voltage (V) (Per Leg)	45
V _{RWM} Max. Working Peak Reverse Voltage (V) (Per Leg)	

Absolute Maximum Ratings

Parameters	Limits	Units	Conditions
I _{F(AV)} Max. Average Forward Current See Fig. 5	30	A	50% duty cycle @ T _C = 87.6°C, square waveform
I _{FSM} Max. Peak One Cycle Non - Repetitive Surge Current (Per Leg)	85	A	@ t _p = 8.3 ms half-sine

Electrical Specifications

Parameters	Limits	Units	Conditions
V _{FM} Max. Forward Voltage Drop (Per Leg) See Fig. 1①	0.72	V	@ 10A
	0.81	V	@ 15A
	1.09	V	@ 30A
	0.68	V	@ 10A
	0.8	V	@ 15A
	1.09	V	@ 30A
	0.62	V	@ 10A
	0.72	V	@ 15A
	0.95	V	@ 30A
I _{RM} Max. Reverse Leakage Current (Per Leg) See Fig. 2①	0.08	mA	T _J = 25°C
	10	mA	T _J = 125°C
C _T Max. Junction Capacitance (Per Leg)	375	pF	V _R = 5V _{DC} (1MHz, 25°C)
L _S Typical Series Inductance (Per Leg)	4.8	nH	Measured from center of cathode pad to center of anode pad

Thermal-Mechanical Specifications

Parameters	Limits	Units	Conditions
T _J Max. Junction Temperature Range	-65 to 150	°C	
T _{stg} Max. Storage Temperature Range	-65 to 150	°C	
R _{thJC} Max. Thermal Resistance, Junction to Case (Per Leg)	3.5	°C/W	DC operation See Fig. 4
R _{thJC} Max. Thermal Resistance, Junction to Case (Per Package)	1.75	°C/W	DC operation
wt Weight (Typical)	1.0	g	
Die Size (Typical)	70X92	mils	
Case Style	SMD-0.5		

① Pulse Width < 300μs, Duty Cycle < 2%




Fig. 1 - Max. Forward Voltage Drop Characteristics (Per Leg)




Fig. 2 - Typical Values of Reverse Current Vs. Reverse Voltage (Per Leg)




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage (Per Leg)




Fig. 4 - Max. Thermal Impedance Z_{thJC} Characteristics (Per Leg)




Fig. 5 - Max. Allowable Case Temperature Vs. Average Forward Current (Per Leg)

