


Description/ Features

The IRKDS408.. Schottky rectifier doubler module has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to 150°C junction temperature. Typical applications are in high current switching power supplies, plating power supplies, UPS systems, converters, free-wheeling diodes, welding, and reverse battery protection.

- 150°C T_J operation
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- UL pending
- TOTALLY LEAD-FREE, RoHS Compliant



Mechanical Description

The Generation V of Add-A-pak module combine the excellent thermal performance obtained by the usage of Direct Bonded Copper substrate with superior mechanical ruggedness, thanks to the insertion of a solid Copper baseplate at the bottom side of the device. The Cu baseplate allow an easier mounting on the majority of heatsink with increased tolerance of surface roughness and improve thermal spread.

The Generation V of AAP module is manufactured without hard mold, eliminating in this way any possible direct stress on the leads.

The electrical terminals are secured against axial pull-out: they are fixed to the module housing via a click-stop feature already tested and proved as reliable on other IR modules.

Major Ratings and Characteristics

| Characteristics | Values | Units |
|--|------------|------------------|
| $I_{F(AV)}$ Rectangular waveform | 200 | A |
| V_{RRM} | 60 | V |
| I_{FSM} @tp = 5 μ s sine | 25500 | A |
| V_F @200Apk, $T_J=125^\circ\text{C}$ | 0.69 | V |
| T_J range | -55 to 150 | $^\circ\text{C}$ |



Voltage Ratings

| Parameters | IRKDS408/060P |
|---|---------------|
| V_R Max. DC Reverse Voltage (V) | 60 |
| V_{RWM} Max. Working Peak Reverse Voltage (V) | |

Absolute Maximum Ratings

| Parameters | Values | Units | Conditions |
|--|--------|-------|--|
| $I_{F(AV)}$ Max. Average Forward Current | 200 | A | 50% duty cycle @ $T_C = 83^\circ\text{C}$, rectangular wave form |
| I_{FSM} Max. Peak One Cycle Non-Repetitive Surge Current | 25500 | A | Following any rated load condition and with rated V_{RWM} applied |
| | 3300 | | |
| E_{AS} Non-Repetitive Avalanche Energy | 15 | mJ | $T_J = 25^\circ\text{C}$, $I_{AS} = 5.5\text{Amps}$, $L = 1\text{mH}$ |
| I_{AR} Repetitive Avalanche Current | 1 | A | Current decaying linearly to zero in 1 μsec Frequency limited by T_J max. $V_A = 1.5 \times V_R$ typical |

Electrical Specifications

| Parameters | Values | Units | Conditions |
|--|--------|------------------|---|
| V_{FM} Max. Forward Voltage Drop (1) | 0.71 | V | @ 200A $T_J = 25^\circ\text{C}$ |
| | 1.03 | V | @ 400A |
| | 0.69 | V | @ 200A $T_J = 125^\circ\text{C}$ |
| | 0.96 | V | @ 400A |
| I_{RM} Max. Reverse Leakage Current (1) | 2.2 | mA | $T_J = 25^\circ\text{C}$ |
| | 650 | mA | $T_J = 125^\circ\text{C}$ $V_R = \text{rated } V_R$ |
| C_T Max. Junction Capacitance | 11000 | pF | $V_R = 5V_{DC}$ (test signal range 100Khz to 1Mhz) 25°C |
| L_S Typical Series Inductance | 5.0 | nH | From top of terminal hole to mounting plane |
| dv/dt Max. Voltage Rate of Change | 10000 | V/ μs | (Rated V_R) |
| V_{INS} RMS isolation voltage (1 sec) | 3500 | V | 50 Hz, circuit to base, all terminals shorted |

(1) Pulse Width < 500 μs

Thermal-Mechanical Specifications

| Parameters | Values | Units | Conditions |
|--|-------------|--------------------|--------------------------------------|
| T_J Max. Junction Temperature Range | -55 to 150 | $^\circ\text{C}$ | |
| T_{stg} Max. Storage Temperature Range | -55 to 150 | $^\circ\text{C}$ | |
| R_{thJC} Max. Thermal Resistance, Junction to Case (Per Leg) | 0.3 | $^\circ\text{C/W}$ | DC operation |
| R_{thCS} Max. Thermal Resistance, case to Heatsink | 0.1 | $^\circ\text{C/W}$ | Mounting Surface, smooth and greased |
| wt Approximate Weight | 110 (4) | gr (oz) | |
| T Mounting Torque $\pm 10\%$ | to heatsink | 5 | Nm |
| | busbar | 4 | |
| Case Style | TO-240AA | | JEDEC |




Fig. 1 - Max. Forward Voltage Drop Characteristics




Fig. 2 - Typical Values Of Reverse Current Vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage




Fig. 4 - Max. Thermal Impedance Z_{thJC} Characteristics




Fig.5 - Max. Allowable Case Temperature Vs. Average Forward Current




Fig.6 - Forward Power Loss Characteristics




Fig.7 - Max. Non-Repetitive Surge Current





Fig.8 - Unclamped Inductive Test Circuit

- (2) Formula used: $T_c = T_j - (Pd + Pd_{REV}) \times R_{thJC}$;
 $Pd = \text{Forward Power Loss} = I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$ (see Fig. 6);
 $Pd_{REV} = \text{Inverse Power Loss} = V_{R1} \times I_R (1 - D)$; $I_R @ V_{R1} = 80\% \text{ rated } V_R$

Outline Table



Ordering Information Table

| Device Code | | | | | | |
|-------------|-----------|--------------------------------|-----------|----------|--------------|-------------------------------------|
| IR | KD | S | 40 | 8 | / 060 | P |
| ① | ② | ③ | ④ | ⑤ | ⑥ | ⑦ |
| 1 | - | International Rectifier | | | | |
| 2 | - | Circuit Configuration | | | | |
| | | | | | | KD = Add-A-Pak - 2 diodes in Series |
| 3 | - | S = Schottky Diode | | | | |
| 4 | - | Average Rating (x10) | | | | |
| 5 | - | Product Silicon Identification | | | | |
| 6 | - | Voltage Rating (060 = 60V) | | | | |
| 7 | - | Lead-Free | | | | |

IRKDS408/060P

Bulletin I27264 rev. A 11/06

International
IOR Rectifier

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level and Lead-Free.
Qualification Standards can be found on IR's Web site.

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 11/06