



ELECTRICAL CHARACTERISTICS: OM300L120CMS (Tc= 25°C unless otherwise specified)

Characteristic	Symbol	Min.	Typ.	Max	Unit
----------------	--------	------	------	-----	------

OFF CHARACTERISTICS

Collector Emitter Breakdown Voltage, VCE=0V	V _{CES}	1200			V
Zero Gate Voltage Drain Current, V _{GE} =0, V _{CE} =1200V	I _{CES}		25		μA
Gate Emitter Leakage Current, V _{GE} =+/-15V, V _{CE} =0V	I _{GES}			2	μA

ON CHARACTERISTICS

Gate Threshold Voltage, V _{CE} =V _{GE} , I _C =6mA	V _{GE(TH)}	4.5		6.5	V
Collector Emitter Saturation Voltage, V _{GE} =15V, I _C =300A	V _{CE(SAT)}			2.6	V

DYNAMIC CHARACTERISTICS

Fwd. Transconductance	V _{CE} =5V, I _C =300A	g _{fs}		70	S
Input Capacitance	V _{GE} =0	C _{ies}		30	nF
Output Capacitance	V _{CE} =25V	C _{oes}		10	nF
Rev. Transfer Capacitance	f=1.0MHz	C _{res}		6	nF

SWITCHING INDUCTIVE LOAD CHARACTERISTICS

Turn-On Delay Time	V _{CC} = 600V, I _C =300A V _{GE} =+15/-10V, R _G =4.7Ω L=100μH, T _j =125°C	t(on)		500	nS
Rise Time		t _r		400	nS
Turn-on Losses		E _{on}			mJ
Turn-off Delay Time		t _{d(off)}		750	nS
Fall Time		t _f		350	nS
Turn-off Losses		E _{off}			mJ

DIODE CHARACTERISTICS


Maximum Forward Voltage	I _F =300A, T _j =25°C T _j =125°C	V _F		2.0	2.8	V
Reverse Recovery Characteristics	V _R =600V, T _j =25°C I _F =300A, T _j =125°C dI/dt=-1500A/μS T _j =25°C T _j =125°C T _j =25°C T _j =125°C	Q _{rr}		15		μC
		I _{rr}		50		A
				70		
		t _{rr}		180		nS
				220		

THERMAL AND MECHANICAL CHARACTERISTICS

Thermal Resistance, Junction to Case (Per IGBT)	R _{thJC}			0.055	°C/W	
Thermal Resistance, Junction to Case (Per Diode)	R _{thJC}			0.11	°C/W	
Maximum Junction Temperature	T _{JMAX}			150	°C	
Isolation Voltage	V _{iSRMS}			2500	V	
Screw Torque	Mounting	-		15	20	in-lb
Screw Torque (M6)	Terminals	-		10	15	in-lb
Screw Torque (M3)	Terminals	-		6	8	in-lb
Module Weight		-		350		Grams

OM300L120CMS

MECHANICAL OUTLINE



EQUIVALENT CIRCUIT

